



**HL70120 Hydraulic Boat Lifts**

### **RGC Advantage**

RGC Hydraulic Boat Lifts combine the physical strength of quality marine grade aluminum with the engineering expertise of the most experienced boat lift manufacturer in the industry.

RGC boat lifts protect your watercraft from damaging wave action, floating debris, weeds, algae and zebra mussels.

Customize your lift with an AC or DC Control Box, Solar Panel, AC Charger, Control Box Shelf, Guide Posts, Canopy, Guide-Ons, Pontoon Cradles, Motor Stop, Extension Legs and many other quality accessories.

### **Applications**

- ▶ Hydraulic Lifts are ideal for waterfront properties with restrictive building ordinances.
- ▶ Most HL lifts can be operated by a 12V or 24V battery powered Hydraulic Control Box. They are the right choice for use in areas with unreliable or no electric service at the dock. A 120V AC Box is also offered. HL90120 lifts require a DC Control Box and function best with the 24V DC model. The HL120132 requires the 24V HD Control Box.
- ▶ HL lifts can safely secure your boat when it is not being used.

### **Features & Benefits**

- ▶ 1,750, 2,000, 4,000, 5,000, 6,000, 7,000, 9,000 and 12,000 lb. lifting capacities.
- ▶ Durable marine-grade aluminum extrusions provide superior strength with minimal maintenance.
- ▶ Corrosion resistant stainless steel hardware increases component life. Silicone bronze nuts on mounting hardware provide easy adjustability.
- ▶ Aluminum hydraulic cylinders and environmentally friendly biodegradable hydraulic fluid are standard for each lift.
- ▶ Both AC and DC control boxes are available for most models.
- ▶ Full length aluminum & vinyl bunks are standard on hydraulic lifts.
- ▶ Large foot plates pivot to adjust to lake beds with a slope.
- ▶ Assembly requires only basic hand tools.
- ▶ A wide array of accessories are available to customize your lift.
- ▶ 15 year limited warranty on aluminum materials and workmanship.



**HL Control Boxes - AC or DC**  
DC Box shown with optional Trickle Charger



**HL1756-60 Hydraulic PWC Lift**



**HL50120-60 Hydraulic Boat Lift w/12V DC Control Box**

## Hydraulic Lift Options

- ▶ 120V AC Hydraulic Control Box
- ▶ 12V DC Hydraulic Control Box
- ▶ 24V DC Hydraulic Control Box
- ▶ 24V DC HD Hydraulic Control Box
- ▶ Control Box Shelf
- ▶ Solar Panels for 12V & 24V Boxes
- ▶ 6 Amp AC Charger
- ▶ Hose Extensions
- ▶ Light Package

- ▶ **Stainless Steel Upgrade Kit** (hydraulic fittings)
- ▶ **Canopies** (acrylic or vinyl)
- ▶ **HL Pontoon Cradles**
- ▶ **HL Tritoon Cradles**
- ▶ **Low Water Roller Kit** (HL5K, HL6K, HL7K & HL9K)
- ▶ **Guide-Ons** (aluminum & wood or aluminum & vinyl - except HL17565 & HL20065)
- ▶ **Bow Stop** (aluminum & vinyl)
- ▶ **Motor Stop** (aluminum & vinyl)
- ▶ **Vertical PVC Guide Posts**
- ▶ **Deep Water Extension Legs**

## Specifications

Model	Weight Capacity	Maximum Beam	Overall Width (incl. feet)	Overall Length (incl. feet)	Lifting Height	Minimum Bunk Height ‡	Hydraulic Cylinders	Shipping Weight (approx.)
HL1765-60	1750 lbs.	65 in.	81 in.	131 in.	60 in.	25 in.	1	235 lbs.
HL20058-48	2000 lbs.	58 in.	74 in.	119 in.	48 in.	24.5 in.	1	215 lbs.
HL20065-48	2000 lbs.	65 in.	81 in.	119 in.	48 in.	24.5 in.	1	225 lbs.
HL40112-48	4000 lbs.	112 in.	129 in.	170 in.	48 in.	25 in.	2	512 lbs.
HL40120-48	4000 lbs.	120 in.	137 in.	170 in.	48 in.	25 in.	2	522 lbs.
HL40112-60	4000 lbs.	112 in.	129 in.	182 in.	60 in.	26 in.	2	522 lbs.
HL40120-60	4000 lbs.	120 in.	137 in.	182 in.	60 in.	26 in.	2	542 lbs.
HL50120-48	5000 lbs.	120 in.	137 in.	191 in.	48 in.	28 in.	2	660 lbs.
HL50120-60	5000 lbs.	120 in.	137 in.	209 in.	60 in.	28.5 in.	2	680 lbs.
HL60112-48	6000 lbs.	112 in.	129 in.	198 in.	48 in.	29.5 in.	2	690 lbs.
HL60120-48	6000 lbs.	120 in.	137 in.	198 in.	48 in.	29.5 in.	2	710 lbs.
HL70112-48	7000 lbs.	112 in.	129 in.	198 in.	48 in.	29 in.	2	720 lbs.
HL70120-48	7000 lbs.	120 in.	137 in.	198 in.	48 in.	29 in.	2	740 lbs.
HL70112-60	7000 lbs.	112 in.	129 in.	209 in.	60 in.	30 in.	2	740 lbs.
HL70120-60	7000 lbs.	120 in.	137 in.	209 in.	60 in.	30 in.	2	760 lbs.
HL90120-48+	9000 lbs.	120 in.	141 in.	200 in.	48 in.	29.5 in.	4	977 lbs.
HL90120-60+	9000 lbs.	120 in.	141 in.	211 in.	60 in.	31 in.	4	997 lbs.
HL120132-48*	12,000 lbs.	132 in.	152 in.	268 in.	48 in.	40 in.	4	1450 lbs.
HL120132-60*	12,000 lbs.	132 in.	152 in.	280 in.	60 in.	40 in.	4	1500 lbs.

‡ Measured from top of bunks to bottom of feet when adjustable legs are fully retracted. Measurements are approximate.

+ HL90120 lifts require a DC control box and operate best with a 24V control box for power.

\* HL120132 lifts require a 24V HD control box for power.